



Atty. Dkt. No. 2102330-991110

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Guthrie, et al.

Serial No. 09/818,092

Group Art Unit: 2817

Filed: March 26, 2001

Examiner: B. Lee

Title: IMPROVED HIGH INTENSITY LIGHT SOURCE

**Certificate of Mailing under 37 CFR 1.8**

*I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as FIRST CLASS MAIL in an envelope addressed to: Commissioner for Patents, Washington, D.C. 20231, on:*

Date 12-13-02 Signature:

Name of person signing certificate:

Derek J. Westberg

\*\*\*

**RESPONSE TO OFFICE ACTION MAILED JUNE 17, 2002**

Commissioner for Patents  
Washington, D.C. 20231

Sir:

In response to the Office Action Mailed June 17, 2002, please amend the application as follows:

12/19/2002 MBERHE 00000004 0001A096

01 FD:2202	252.00 OF
02 FD:2201	126.00 OF
03 FD:1000	440.00 OF

**AMENDMENTS IN CLEAN FORM**

In the Drawings:

*Please replace the drawings filed on June 14, 2001, with the attached two sheets of formal drawings.*

In the Written Description:

*Please replace the paragraph on page 6, lines 13-24 with the following:*

The sapphire window 34 may function as a "light integrator" for transmitting the light of the plasma lamp from the chamber, for example, to application-specific optics. The tapered, conical sapphire window 34 may be sealed against the surrounding ceramic material forming the channel 30 by coating the outside edges of the sapphire window with a material such as glass containing MgO, or alternatively, with  $\text{SiO}_3$  or  $\text{SiO}_2$ . Next the mating surfaces of both the window and the ceramic channel may each be coated with a thin layer of metallic material, such as copper, a copper alloy, or platinum. Then a piece of preferably pure platinum wire may be placed between the two thin film layers. Finally, a laser is used to heat the wire, and thereby melt the metallic material and bond the layers together.

*Please replace the paragraph on page 7, lines 9-26 with the following:*

Figure 2 shows a second embodiment of a lamp in accordance with the invention which is somewhat similar to Figure 1 except that the gas housing has an integrated RF energy structure. In Figure 2, the elements are designated similarly to Figure 1, using like reference numerals for like elements. The gas fill chamber 24 may be housed in a gas housing 20 preferably comprising a ceramic material 22 and provided with a light transmissive window 34, preferably of a tapered rod of sapphire as previously described and a fill plug 38. In this embodiment, an RF energy structure such as one or more coils

is used to create a plasma discharge. In this way, the RF structure of the plasma lamp that is active with

radio wave energy is integral with the ceramic housing 20 that contains the plasma gas fill. This integration of the RF structure of the plasma lamp and the gas housing into a single structure, as shown, improves the coupling of RF energy to the gas, and allows significant gains in lamp efficiency and compactness.

*Please replace the paragraph on page 7, lines 27-30 with the following:*

The second embodiment may also comprise segments of ferrite material 41 placed adjacent the coils 36 in order to help concentrate the magnetic field associated with the coils 36 on the gas fill. An illustration of this embodiment is shown in Figure 7, in which like reference numerals are used for like elements of Figure 2.

*Please replace the paragraph on page 9, lines 15-23 with the following:*

Figures 4A and 4B show a fourth embodiment of a light source in accordance with the invention. A gas housing 60 (see Fig. 4B) for the gas fill is formed so as to be integral with a cylindrical resonant waveguide structure 62 comprising ceramic material. Because a separate bulb is not used, the gas housing 60 and waveguide 62 comprise a single, integrated structure. A source of radio wave radiation 64 (see Fig. 4B) may be disposed near one end of the waveguide, while the gas housing is formed at an opposite end. The gas housing 60 may include a window 66 preferably made from sapphire.